LED BAY LIGHT

VENUS Series



FEATURES & BENEFITS

- Traditional bay light appearance with advanced LED system.
- Rugged extruded aluminum housing.
- Reflector with outstanding illumination for open floor plan.
- Chain, cable, hook mount.
- High quality LEDs, driver and components, e.g. MOLEX, WAGO connectors.
- Multiple lighting control options are available, e.g. motion sensor, 1-10V.
- 5 years limited warranty available.

VENUS Series combines a unique optic solution with traditional bell-shaped appearance, which out- performs traditional high-bay and conventional COB LED bay lights.



CERTIFICATIONS

UL/ CUL/ DLC/ LM79/ CE/ RoHS

TECHNICAL PARAMETERS

Power	40/60/90/120/160/200W			
Input	90-305 VAC			
PF	>0.95			
THD	<15%			
L85	>50,000H			
Operating Temperature	-40F to 104F			
Efficacy	110-130lm/W			
ANSI CCT	4000K/5000K			
Min CRI	80			
IP Rating	IP43			
SPD	Optional			
DALI	/			
1-10V	Optional			
Photocell	/			
Smart Control	Optional			
Optic (IESNA)	T5R			
Color Options	Black / Grey			

 * No foreign objects shall be placed within 5 feet (1.5m)of the fixture from any direction.

ORDERING INFORMATION

Example : BLD200-T5R-50K-BK-00

MODEL (Norminal Power)	OPTIC	сст	OPTIONAL	LIGHTING
90-305VAC	LENS	(ANSI)	COLOR	CONTROL
BLD40 BLD60 BLD90 BLD120 BLD160 BLD200	T5R	40K ★ 50K	★ BK* GR	00 Not required 02 Motion Sensor 05 1-10V dimming