SP-SL480W-6[™]





The SP-SL480W-6 is a solar powered LED light tower that provides a safe and effective way for operators to quickly deploy high powered lights. This light allows for easy transportation and easy setup. Unlike other types of lamps, this one has LED light. These types of lights have a much longer lifetime than a normal bulb. Our portable, solar powered light trailer helps you to reduce your energy consumption, and it will illuminate large areas at great distances.

Uses and Applications Guide

Streets lighting	
Parking lots	
Concert	
Construction Zones	
Public parks	
Emergency Lights	
Access roads	



Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or an commection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage.

Technical Specifications SP-SL480W-6 Light Details

Led Lights Output:	6*80 W(480 W)
Led Lights Service Life:	50000 H

Solar Panel System

Solar Panel Output:	4*260 W(1040 W)
Solar Panel Material:	Monocrystal Silicon
Controller:	МРРТ

Solar Battery

Model:	Gel Deep Cycle
Quan and Capacity of Battery:	6*150 AH(900 AH)
Output Voltage:	DC 12V
Material:	Colloid
Charging Time of Solar Panel:	8-10 H
Working Time:	18-24 H

Mast & Trailer Details

Mast Lifting Operation:	Manual Winch
Mast Lifting Height	up to 19.6FT
Windproof Ability:	62 MPH
Trailer:	Single Axle Trailer
Trailer:	Single Axle Trailer

Size & Weight

Packing size(L*W*H)in:	90.5*78.7*90.5
Net Weight:	2314 lbs