



The SolarPath HighLight HL-SL-AUR™ is the premier LED solar illumination technology in its class today. Ultra-bright/High Intensity LED lighting means a total lighting solution for any need. This product has both a solar engine and a street light. The HL-SL-AUR's battery and control is on the LED head which allows this product to be used for parks, roads, path. Once the product is installed, it can be controlled via a remote control.

Key features:

- Low installation and maintenance costs.
- IP67 Rating.
- High LED performance 1W/140lm.
- Light dimming engine.
- Led's operating life time over 150,000 hours at maximum output.
- Dedicated optical lens per LED for enhanced spread and uniformity.
- LED strings shunt protection.
- Ideal for solar or energy saving electrical applications.
- Battery enclosure
- Aluminum housing for efficient heat dissipation
- Approved IDA
- LM 79/80

Uses and Applications Guide

Mid-size roads	●
Boardwalks	●
Farms	●
Public parks	●
Access roads	●
Walking paths	●
Roads	●

Technical Specifications

Lighting and Operation

Lighting Technology	LED Street Light Technology
Brightness	Up to 8,400 Lumen
Color temperature	5,500°K (other may be available upon request)
Available distribution types	III
Standard operation features	<ul style="list-style-type: none"> • Automatic day/night detection • Battery deep discharge and overcharge protection • False activation prevention logic • Computerized self-learning seasons change detection • Auto-adjusting battery charge algorithm according to ambient temperature sensing
Operation time	up to 72 hours (per charge cycle, programming dependent)

Energy Collection and Storage

Solar panel type	Mono/ Poly Crystalline Silicon
Battery type	Lithium
Voltage / Current	12VDC

Materials

Body	Galvanized Steel/Stainless steel and Aluminum
Dimensions (main body)	Depends on configuration
Unit weight	Depends on configuration
EPA	Depends on configuration
IP Rating	IP67

Optional Features

Integrated Motion Option	Allows for flexible energy saving programming for location with low insolation levels and extreme weather conditions.
--------------------------	---

Ordering Guide

EXAMPLE: HL-SL-AUR-45W-15W-1-30K-192WH-1-GR-00

Model	Solar Panel Quantity	Solar Panel	LED Power	Distribution type	LED Color Temp	Battery Options	Arm	Body Color	Options
HL-SL-AUR	A- 1 Panel B- 2 Panel	45W 60W 80W 100W 120W 140W 180W 200W	15W 20W 30W 40W 50W 60W	3 - Type III	30K 40K 50K 57K	192WH 312WH 460WH 680WH	1 - Single 2 - Double	GR - Grey	00 - not required 01 - motion sensor



*Up on Request

www.solarpathusa.com | 1 888 333

Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other than downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage.