

## Technical Specifications

The SolarPath HighLight NPSL™ is the premier LED solar illumination technology in its class today. Ultra- bright/High Intensity LED lighting means a total lighting solution for any need. This product has both a solar engine and a street light. The HL-NPSL's battery and control is on the LED head which allows this product to be used for parks, roads, path. Once the product is installed, it can be controlled via a remote control.


### Key features

- Low installation and maintenance costs.
- IP 67 Rating.
- High LED performance 1W/130lm.
- Light dimming engine.
- Led's operating life time over 150,000 hours at maximum output.
- Dedicated optical lens per LED for enhanced spread and uniformity.
- LED strings shunt protection.
- Ideal for solar or energy saving electrical application.
- Battery enclosure.
- Aluminum housing for efficient heat dissipation
- Approved IDA.
- LM 79/80

Solar Module Parameters	Type	High-efficiency Monocrystalline Silicon
	Power	Up to 300W
Solar ChargeController Parameters	Type	MPPT, infrared solar charging controller with infrared remote control.
	LifePO4	Up to 1,198WH
LED Light Parameters	Light Source Power	Up to 120W
	Lamp Rated Total Luminous Flux	Up to 15,800lm
	CCT (Correlated Color Temperature)	3,000K-6,000K
	Color Rendering Index (CRI)	≥81
LED Light Parameters	Light Control Voltage	36VDC
Control Modes	Manual ON/OFF / Automatically ON/OFF / Time Control	
Operation profile	Depend on installation area, can be programed with remote control.	
Lighting Material	Die-casting Aluminum	
Extended Application	Wireless Remote controller	
Optional	GPRS Integrated Management System( Remote control and monitoring)	
Product size	light body	31.4 * 12.2 * 4.5 (inch)
	solar panel	Depend On Solar Panel wattage
Net weight	light body	Depend On LED power
	solar panel	Depend On Solar Panel Wattage

### Uses and Applications Guide

Streets lighting	●
Parking lots	●
High Speed way	●
Branch roads	●
Residential roads	●
Public parks	●
Sports lighting	●



### Ordering Guide

EXAMPLE: NPSL-A-120W-40W-3-30K-840WH-1-GR

Model	Solar Panel Quantity	Solar Panel	Led Power	Distribution Type	Led Color Temp	Battery options	Arm	LED Body color	Motion Sensor
NPSL	A – 1 B – 2	120W 150W 200W 250W 280W 300W	40W 50W 60W 70W 80W 90W 100W 120W	1 – Type I 2 – Type II 3 – Type III 4 – Type IV 5 – Type V	30K 40K 50K 60K	616WH 693WH 760WH 845WH 1014WH 1198WH	1 – Single 2 - Double	GR - Grey	00 – no motion sensor 01 – motion sensor



\*Up on request

LegalClarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be altered and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alteration or any kind of use other than downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage

