



LED LINEAR LIGHT

BRIGHT-A Series



BRIGHT-A is designed to replace up to 400W HPS lamps. Traditional in appearance while providing unmatched overhead lighting performance and energy savings.



FEATURES & BENEFITS

- Rugged extruded aluminum housing.
- Double wings enlarge heat dissipation area which provides exceptional thermal management.
- Corrosion resistant polyester powder painted 100µm thickness.
- Surface mount and suspension mount available.
- High quality LEDs, driver and components, e.g. MOLEX, WAGO connectors.
- Multiple lighting control options are available, e.g. motion sensor, 1-10V.
- 5 years limited warranty available.

CERTIFICATIONS

UL/ CUL/ DLC/ LM79/ CE/ RoHS

TECHNICAL PARAMETERS

Power	120/160/200W
Input	90-305 VAC
PF	>0.95
THD	<15%
L85	>50,000H
Operating Temperature	-40F- 122F
Efficacy	110-130lm/W
ANSI CCT	3000K/4000K/5000K
Min CRI	80*
IP Rating	IP43
SPD	Optional
DALI	/
1-10V	Optional
Photocell	/
Smart Control	/
Optic (IESNA)	Type V
Color Options	White

* Standard

ORDERING INFORMATION

Example : BLA120-T5D-50K-WH-00

MODEL (Nominal Power)	OPTIC LENS	CCT (ANSI)	OPTIONAL COLOR	LIGHTING CONTROL
90-305VAC				
BLA120 BLA160 BLA200	T5D	30K 40K ★ 50K	★ WH	00 Not required 02 Motion Sensor 05 1-10V dimming

★ Regularly stocked item