



# LED LINEAR LIGHT

## BRIGHT-B Series



The BRIGHT-B fixture is an ideal LED solution to Replace existing fluorescent troffers with Multiple mounting options, available in Different power range.



### FEATURES & BENEFITS

- Compact and sleek design.
- Rugged extruded aluminum housing.
- Corrosion resistant polyester powder painted 100µm thickness.
- Surface mount and suspension mount available.
- Multiple units are linkable.
- Multiple lighting control options are available, e.g. motion sensor, 1-10V.
- Emergency Power Supply (EPS) available.
- 5 years limited warranty available.

### CERTIFICATIONS

UL/ CUL/ DLC/ LM79/ CE/ RoHS

### TECHNICAL PARAMETERS

Power	40/60/90W
Input	90-305 VAC
PF	>0.95
THD	<15%
L85	>50,000H
Operating Temperature	-40F- 122F
Efficacy	110-130lm/W
ANSI CCT	3000K/4000K/5000K
Min CRI	80*
IP Rating	IP20
SPD	Optional
DALI	/
1-10V	Optional
Photocell	/
Smart Control	/
Optic (IESNA)	Type V
Color Options	White

\* Standard

### ORDERING INFORMATION

Example : BLB40-T5D-40K-WH-00

MODEL (Nominal Power)	OPTIC LENS	CCT (ANSI)	OPTIONAL COLOR	LIGHTING CONTROL
90-305VAC				
BLB40 BLB60 BLB90	T5D	30K 40K ★ 50K	★ WH	Emergency Power Supply (EPS)

★ Regularly stocked item