SPTR-F





FEATURES & BENEFITS

- High lumen output and high mounting height solution.
- Thermal control system to ensure long lifetime.
- Tool free design for easy installation and maintenance.


CERTIFICATIONS

CE CB SAA 🔊 IP66 IK09 LM

The SOLARPATH SPTR-F $^{\rm m}$ is the premier LED solar illumination technology in
its class today. Ultra-bright/High Intensity LED lighting means a total lighting
solution for any need. The lighting fixture can be use up to 80W and can be
controlled via remote control.

TECHNICAL PARAMETERS

Power	30W-80W			
Input	AC90-305 V or AC220-240 V or 12/24DCV			
PF	>0.95 cos			
L85	Up to 100,000 hrs.			
Operating Temperature	-31F- 122F			
Efficacy	143lm/W			
ANSI CCT	3000K/4000K/Amber			
Min CRI	70* or 80			
IP Rating	IP66			
Timing	Optional			
DALI	Optional			
1-10V	Optional			
PWM	Optional			
Optic (IESNA)	Type VI, Type V			
Optic	PC (standard) / PMMA (option)			
Color Options	Black (*Other colors up on request)			
Material	Die cast Aluminum			



Ordering Guide

EXAMPLE: SPTR-F-30W-4-30K-BLK-00

LED Type	MODEL (Nominal Power) AC90-305 V or AC220-240 V or 12/24DCV	OPTIC LENS	CCT (ANSI)	OPTIONAL COLOR	LIGHTING CONTROL
SPTR-F	30W 40W 50W 60W 80W	4- Type VI 5- Type V	 ★ 30K ★ 40K ★ 60K ★ Amber * Other colors available 	★BLK * Other colors available	00 No motion sensor 01 Motion Sensor 04 DALI 05 1-10V dimming

Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade na