

LED STREET LIGHT

FIND Series



Employing a mix of traditional exterior design elements with modern power-saving technologies, the FIND series offers exceptional energy efficiency for faster ROI while providing an aesthetic appeal.

FEATURES & BENEFITS

- Single-cast aluminum housing enables passive heat dissipation along the entire length of the luminaire.
- Modular design allows for easy installation, replacement and maintenance.
- Corrosion resistant polyester powder painted 100µm thickness.
- Meets a 1000-hour salt spray certification per ASTM B117/ ISO 9227:2012.
- Class II isolation protection.
- 0 and +5 degree of titling angle adjustment.
- Adjustable for 1 5/8-2 3/8" (42mm-60mm) O.D. Tenon.
- Multiple smart lighting control options are available, e.g. photocell, 1-10V.
- 5 years limited warranty available.

CERTIFICATIONS

UL/ CUL/ DLC/ LM79/ CB/ CE/ RoHS

TECHNICAL PARAMETERS

Power	20- 120W
Input	120-277VAC or 220-240VAC or 12-24VDC
PF	>0.95
THD	<20%
L85	>200,000H/>60,000H
Operating Temperature	-40F- 122F
Efficacy	120-160lm/W
ANSI CCT	3000K/4000K/5000K/5700K
Min CRI	70* or 80 or 90
IP Rating	IP65
SPD	10KA* or 20KA
DALI	/
1-10V	Optional
Photocell	Optional
Smart Control	Optional
Optic (IESNA)	Type II, Type III, Type IV, Type V
Color Options	Grey

* Standard

ORDERING INFORMATION

Example : SLG60-T2M-50K-GR-05

MODEL (Nominal Power)				OPTIC LENS	CCT (ANSI)	OPTIONAL COLOR	LIGHTING CONTROL	ACCESSORY INFO
120-277VAC or 220-240VAC	12-24VDC	120-277VAC or 220-240VAC	12-24VDC					
SLG16 SLG25 SLG40 SLG60	SLG30D* SLG40D*	SLE60 SLE80 SLE90 SLE120	SLE60D* SLE80D*	T2M T3L T4M T5U T5V T5W T5S T5M T5L T5X T5D	30K ★ 40K ★ 50K 57K	★ GR	00 Not required 01 Photocell 05 1-10V dimming	Adaptor Bracket 3/5/7-pin NEMA Receptacle 20KA Surge Protection Device Safety Cable

* 1-10V dimming unavailable

★ Regularly stocked item