HIGHLIGHT BELL





The SolarPath HIGHLIGHT BELL[™] is the premier LED solar illumination technology in its class today. Ultrabright/High Intensity LED lighting means a total lighting solution for any need.

This product has both a solar engine and a street light. The HIGHLIGHT BELL's battery and control is on the LED head which allows this product to be used for parks, roads, path. Once the product is installed, it can be controlled via a remote control.

Key features:

- Low installation and maintenance costs.
- IP67 Rating.
- High LED performance 1W/140lm.
- Light dimming engine.
- Led's operating life time over 150,000 hours at maximum output.
- Dedicated optical lens per LED for enhanced spread and
- uniformity.
- LED strings shunt protection.
- Ideal for solar or energy saving electrical applications.
- Battery enclosure
- Aluminum housing for efficient heat dissipation
- IDA Approved

Uses and Applications Guide

Mid-size roads	
Boardwalks	
Farms	
Public parks	
Access roads	
Walking paths	
Roads	

Technical Specifications

Lighting and Operation

ighting Technology	LED Street Light Technology				
Brightness	Up to 14,837 Lumen				
Color temperature	5,500°K (other may be available upon request)				
vailable distribution types	II, V				
tandard operation features	 Automatic day/night detection 				
	 Battery deep discharge and overcharge protection 				
	 False activation prevention logic 				
	Computerized self-learning seasons change detection				
	 Auto-adjusting battery charge algorithm according to ambient temperature sensing 				
Operation time	up to 72 hours (per charge cycle, programming dependent)				

Mono/ Poly Crystalline Silicon, Up to 600W					
Extreme temperature Deep Cycle AGM / Gel-Cell					
12VDC/24VDC					
Galvanized Steel/Stainless steel and Aluminum					
Depends on configuration					
Depends on configuration					
Depends on configuration					
IP67					
Allows for flexible energy saving programming for location with low insolation levels and extreme weather conditions.					

Ordering Guide: EXAMPLE: HIGHLIGHT-BELL-A-50W-20W-2-30K-A-50AH-1-GR-00

Model	Solar Panel Quantity	Solar Panel	LED Power	Distribution type	LED Color Temp	Battery qty.	Battery Options	Arm	Body Color	Options
HIGHLIGHT BELL	A- 1 Panel B- 2 Panels C- 3 Panels D- 4 Panels	50W 65W 85W 100W 125W 135W 180W 200W	20W 30W 40W 60W 80W 100W	2- Туре II 5- Туре V	30K 40K 50K 57K	A-1 B-2 C-3 D-4	50AH 75AH 80AH 100AH 150AH 180AH	1 – Single 2 - Double	GR – Grey BLK- Black BZ- Bronze WH- White Custom	00 - not required 01 - motion sensor 02 - AC- Hybrid



www.solarpathusa.com | 1 888 333

Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trade marks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all others, ad/or downloadable documents, and/or downloadable contents, is strictly prohibited without express written permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage.