

HIGHLIGHT HL-ML-ASL

The design of solar street light / courtyard light absorbs energy from the universe, and combines it with high efficiency solar panel, LEDs, and Lithium battery. It adopts advantage technics such as micro-controller, human infrared sensor and so on and combines with integrated design to achieve multiple features such as low power consumption but high brightness, long lifespan and maintenance free, meanwhile with waterproof function and great thermal dissipation. The intelligent control can be reprogrammed from the ground with an infrared before and after install. It is one of our great innovation patented products.



Key features:

- Low installation and maintenance costs.
- IP65 Rating.
- High performance LEDs with 190lm/w.
- Light dimming engine.
- Led's operating life time over 100,000 hours at maximum output.
- Adjustable mounting bracket.
- Adjustable LED.
- LED strings shunt protection.
- Ideal for solar or energy saving electrical applications.
- Aluminum housing for efficient heat dissipation

Technical specifications

Solar Module Parameters	Type	Monocrystalline Silicon
	Power	Up to 220W
Solar Charge Controller Parameters	Type	MPPT
Battery Parameters	Type	LifePO4
	Capacity	Up to 48AH
LED Light Parameters	Light Source Power	Up to 200W
	Lamp Rated Total Luminous Flux	Up to 38,000lm
	Luminous Efficacy	190lm/w
	CCT (Correlated Color Temperature)	2,500K-6,500K
	Color Rendering Index (CRI)	≥ 70
Operation profiles	* Operation profile above are active depending to the solar radiation in the installation location, please consult with one of Solarpath representative.	
Lighting Material	Die-casting Aluminum	

Uses and Applications Guide

Mid-size roads	●
Streets lighting	●
Parking lots	●
Boardwalks	●
Farms	●
Public parks	●
Private gardens	●
Access roads	●
Walking paths	●



Ordering Guide: EXAMPLE: HIGHLIGHT HL-ML-ASL-45W-20W-1-25K -12AH-BLK-00

Model	Solar Panel	LED Power	Distribution type	LED Color Temp	Battery Options	Body Color	Options
HIGHLIGHT HL-ML-ASL	40W	20W	1 – Type I	25K	18AH	BLK- Black	00- No motion sensor 01- Motion sensor
	45W	30W	2- Type II	30K	24AH		
	55W	40W	3- Type III	40K	30AH		
	65W	50W	4 – Type IV	50K	36AH		
	85W	60W	5 – Type V	65K	42AH		
	95W	80W			48AH		
	100W	90W					
	120W	100W					
	140W	120W					
	175W	150W					
	200W	180W					
	220W	200W					



*Up on request.

Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other than downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage.