# HIGHLIGHT HL-SL-S Specifications





# Whyus?

#### **Innovative Technology**

High-efficiency solar and advanced LEDs deliver superior performance, long life, and maximum ROI.

#### **Photometric**

We conduct photometric measurements on all our products to ensure optimal performance and compliance with industry standards

#### **Versatile Lightning**

We designs and install solar-powered lightning systems tailored for all kind of locations such as streets, parks, pathways, homes, etc.

#### **Global Reach**

Worldwide success proves our adaptability and regulatory expertise.

#### **Sustainable Savings**

These solutions enhance safety, promote sustainability and providing significant energy and cost saving.

SolarPath is dedicated to delivering architectural and commercial-grade solar lighting that can be customized to meet specific client requests, both in technical specifications and aesthetic design, ensuring a perfect fit for a diverse range of needs.

#### Warranty







The SolarPath HIGHLIGHT HL-SL-S<sup>TM</sup> is the premier LED solar illumination technology in its class today. Ultra-bright/High Intensity LED lighting means a total lighting solution for any need. Whether the goal is large area or mid-size to major roadway clarity, our intense and bright full-spectrum lighting the HIGHLIGHT HL-SL-S<sup>TM</sup> brings solar lighting performance and sustainability to the next level.





#### **Technical specification**

	Tennical specification								
Solar Module	Type	High-efficiency Monocrystalline Silicon							
Parameters	Power	Up to 700W							
Solar Charge Controller	MPPT (Maximum Power Point Tracking), infrared solar charging controller								
Battery	Extreme temperature Deep Cycle AGM / Gel-Cell	Up to 250AH							
	Battery Enclosure	Mount at Top/Middle Or In-Ground Pole (Depends on battery Weight)							
	Light Source Power	Up to 100W (Up to 19,500 lm)							
LED Light Parameters	CCT (Correlated color temperature)	3,000K-5,700K/ Amber							
	Distribution type	Type I, II, III, IV,V							
<b>Operation Time</b>	Up to 72 hours (per charge cycle, programming dependent)								
Standard Operation									
	<ul> <li>Battery deep discharge and overcharge protection</li> </ul>								
	•False activation prevention logic								
	•Computerized self-learning seasons change detection								
	•Auto-adjusting battery charge algorithm ad	ecording to ambient temperature sensing							
IP Rating	IP67								
Integrated Motion Option	Allows for flexible energy saving programming for location with low insolation levels and extreme weather conditions.								
<b>Product Size</b>	Light Body	Depend On LED power							
1 Toutet SIZE	Solar Panel	Depend On Solar Panel wattage							
Net Weight	Light Body	Depend On LED power							
	Solar Panel	Depend On Solar Panel wattage							



#### **FIXTURE FEATURES**

- Low installation and maintenance costs.
- IP67 Rating.
- High performance 143lm/w.
- Light dimming engine.
- Led's operating life time over 100,000 hours at maximum output.
- Dedicated optical lens per LED for enhanced spread and uniformity.
- LED strings shunt protection.
- Ideal for solar or energy saving electrical applications.
- Battery enclosure
- Aluminum housing for efficient heat dissipation
- IDA Approved
- LM 79/80





### **SOLAR STREET LIGHT**

USES AND APPLICATIONS GUIDE						
Streets Lighting						
Parking Lots						
Residential Roads						
Public Parks						
Sports Lighting						



#### **ORDERING GUIDE**

Ordering Guide: EXAMPLE: HIGHLIGHT HL-SL-S-A-50W-SLA-25W-1-30K-A-50AH-PM-GR-1-00

Model	Solar Panel Qty	Solar Panel	LED Head	LED Power	Distribution type	LED Color Temp	Battery Quantity	Battery Options	Battery enclosure	Body Color	Arm	Options
HL-SL-S	A - 1 Panel	50W	SLA	25W	1-Type I	30K	<b>A</b> - 1	50AH	PM-Mounted to pole	GR- Gray	1-single	00- not required
	B- 2 Panel	65W	SLB	30W	2-Type II	40K	<b>B-</b> 2	75AH	GM-Placed on ground beside	BK- Black	2-double	01- motion sensor
	C- 3 Panel	85W	SLG	40W	3-Type III	50K	C- 3	85AH	pole	BZ- Bronze		
	D- 4 Panel	100W	SRS	60W	4-Type IV	57K	D- 4	100AH		WH- White		
		125W	SRL	80W	5-Type V	Amber		125AH		Custom		
		135W	SKA	90W				150AH				
		150W	FLA	120W				180AH				
		160W	FLW	150W				200AH				
		180W	FLT					250AH				
		200W	ARS									
		250W										
		300W										
		350W										

Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trade marks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, con- tainted herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage



## Contact us

+1.201.490.4499

Toll free: 1.888.333.SOLAR (7652)

contact@solarpathusa.com

www.solarpathusa.com