HIGHLIGHT SP-SBL Specifications





Whyus?

Innovative Technology

High-efficiency solar and advanced LEDs deliver superior performance, long life, and maximum ROI.

Photometric

We conduct photometric measurements on all our products to ensure optimal performance and compliance with industry standards

Versatile Lightning

We designs and install solar-powered lightning systems tailored for all kind of locations such as streets, parks, pathways, homes, etc.

Global Reach

Worldwide success proves our adaptability and regulatory expertise.

Sustainable Savings

These solutions enhance safety, promote sustainability and providing significant energy and cost saving.

SolarPath is dedicated to delivering architectural and commercial-grade solar lighting that can be customized to meet specific client requests, both in technical specifications and aesthetic design, ensuring a perfect fit for a diverse range of needs.

Warranty





HIGHLIGHT SP-SBL TM solar billboard light is the ideal LED solar illumination technology for billboard, signs applications. The system is operating automatic with maintenance free.











Product size

Technical specification							
Solar Module	Type	High-efficiency Monocrystalline Silicon					
Parameters	Power	Up to 17W					
Solar Charge Controller	MPPT (Maximum Power Point Tracking), infrared solar charging controller						
Battery	LifePO4	Up to 35AH					
LED Light Parameters	Light Source Power	Up to 10W (Up to 2,000 lm)					
	CCT (Correlated color temperature)	3,000K-6,000K					
	Dual CCT (Can change by push button)						
	CRI (Color rendering index)	<u>≥</u> 82					
Working Mode	First 4hr- 100%, than 25% till dawn.						
IP Rating	IP65						
Material	Al · · · · · · · · · ·						

Aluminum Die-casting

Depend on LED and Panel wattage



USES AND APPLICATIONS GUIDE				
Billboards				
Signs				
Monuments				

Key features:

- Low installation and maintenance costs.
- Replaceable Battery.
- IP65 Rating.
- Light dimming engine.
- Led's operating life time over 100,000 hours at maximum output.
- LED strings shunt protection.
- Ideal for solar or energy saving electrical applications.
- Aluminum housing for efficient heat dissipation.
- IDA Approved.



ORDERING GUIDE

Ordering Guide: HIGHLIGHT-SP-SBL-11W-5W-30K-8AH-BLK-23.62"

Model	Solar Panel	LED Power	LED color temp.	Battery capacity	Body color	Fixture Length
SP-SBL	5W	2.5W	30K	8AH	BLK-Black	11.81"
	11W	5W	40K	17AH	SLV-Silver	23.62"
	13W	7.5W	50k	26AH		35.43"
	17W	10W	60K	35AH		47.24"

Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trade marks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, con- tainted herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage



Contact us

+1.201.490.4499

Toll free: 1.888.333.SOLAR (7652)

contact@solarpathusa.com

www.solarpathusa.com