HIGHLIGHT SP-SDGL-M Specifications





Whyus?

Innovative Technology

High-efficiency solar and advanced LEDs deliver superior performance, long life, and maximum ROI.

Photometric

We conduct photometric measurements on all our products to ensure optimal performance and compliance with industry standards

Versatile Lightning

We designs and install solar-powered lightning systems tailored for all kind of locations such as streets, parks, pathways, homes, etc.

Global Reach

Worldwide success proves our adaptability and regulatory expertise.

Sustainable Savings

These solutions enhance safety, promote sustainability and providing significant energy and cost saving.

SolarPath is dedicated to delivering architectural and commercial-grade solar lighting that can be customized to meet specific client requests, both in technical specifications and aesthetic design, ensuring a perfect fit for a diverse range of needs.

Warranty





The SolarPath HIGHLIGHT SP-SDGL-MTM is the most advanced and sophisticated solar light pole available on the market. The solar light pole is completely off-grid and works autonomously, using sustainable solar power. This means there is no need for expensive cabling and invasive trenching, which results in fast installation, easy operation and a low total cost of ownership. Solar energy generated during the day is stored in high-quality lithium batteries, which are long-lasting and require minimum maintenance. The highly efficient LED-luminaire provides powerful lighting at night.



HIGHLIGHT SP-SDGL-M

700 1 · 1	9.09 4.9
Technical	specification
1 CCIIIICAI	SUCCINCACION

Technical specification								
Solar Module	Туре	Monocrystalline solar panel						
Parameters	Power	45W						
Solar Charge Controller	MPPT (Maximum Power Point Tracking), infrared solar charging controller							
Battery	LifePO4	60AH						
	Light Source Power	30W (Up to 4,000 lm)						
LED Light Parameters	CCT (Correlated color temperature)	3,000K/6,000K						
Operation profile	Dusk to dawn (dim per to solar radiation)							
IP Rating	IP65							
LED head material	Die-casting aluminum Led Light head + PC							
Pole height (Recommended)	Up to 16 FT							
(pole not included)								



SOLAR STREET LIGHT

USES AND APPLICATIONS GUIDE				
Branch roads				
Residential Roads				
Public Parks				
Walking/bike path				
Street Lighting				



ORDERING GUIDE

Ordering Guide: EXAMPLE: SP-SDGL-M-45W-30W-30K-60AH-11FT-BLK

Model	Solar panel	LED Power	Color Temperature	Battery capacity	Pole height	Body color
SP-SDGL-M	45W	30W	30K	60AH	11FT	BLK-Black
			60K		13FT	
					16FT	

Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trade marks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, con- tainted herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage



Contact us

+1.201.490.4499

Toll free: 1.888.333.SOLAR (7652)

contact@solarpathusa.com

www.solarpathusa.com