

# HIGHLIGHT SP-WPTX

## Specifications



## Why us?

### **Innovative Technology**

High-efficiency solar and advanced LEDs deliver superior performance, long life, and maximum ROI.

### **Photometric**

We conduct photometric measurements on all our products to ensure optimal performance and compliance with industry standards

### **Versatile Lighting**

We design and install solar-powered lighting systems tailored for all kinds of locations such as streets, parks, pathways, homes, etc.

### **Global Reach**

Worldwide success proves our adaptability and regulatory expertise.

### **Sustainable Savings**

These solutions enhance safety, promote sustainability and provide significant energy and cost savings.

### **Warranty**


SolarPath is dedicated to delivering architectural and commercial-grade solar lighting that can be customized to meet specific client requests, both in technical specifications and aesthetic design, ensuring a perfect fit for a diverse range of needs.



The SOLARPATH HIGHLIGHT SP-WPTX™ is the most advanced and sophisticated solar light pole available on the market. The solar light pole is completely off-grid and works autonomously, using sustainable solar power. This means there is no need for expensive cabling and invasive trenching, which results in fast installation, easy operation and a low total cost of ownership. Solar energy generated during the day is stored in high-quality lithium batteries, which are long-lasting and require minimum maintenance. The highly efficient LED-luminaire provides powerful lighting at night.

## Technical specification

|                         |                                                                         |                                                  |
|-------------------------|-------------------------------------------------------------------------|--------------------------------------------------|
| Solar Module Parameters | Type                                                                    | CIGS Amorphous flexible solar panel wrap on pole |
|                         | Power                                                                   | Up to 720W                                       |
|                         | Amount of solar modules                                                 | Up to 4 pcs                                      |
| Solar Charge Controller | MPPT (Maximum Power Point Tracking), infrared solar charging controller |                                                  |
| Battery                 | LifePO                                                                  | Up to 150AH                                      |
| LED Light Parameters    | Light Source Power                                                      | Up to 50W (Up to 6,500 lm)                       |
|                         | CCT (Correlated color temperature)                                      | 3,000K-6,000K/Amber                              |
|                         | CRI (Color rendering index)                                             | <u>≥81</u>                                       |
| Control Modes           | Manual ON/OFF / Automatically ON/OFF / Time Control                     |                                                  |
| Operation profile       | Dusk to dawn (Depend on solar radiation)                                |                                                  |
| IP Rating               | IP65                                                                    |                                                  |
| Operation Temperature   | -31°F~122°F                                                             |                                                  |



# FLEX SERIES -1.7N

CIGS Flexible Modules:  
High Power Density in a Flexible Form Factor

## Solar cylindrical wrap pole panel data sheet

### Key Features

- Record efficiency level in a CIGS flexible form factor.
- Low installed weight at less than  $2.9 \text{ kg/m}^2$  ( $<0.6 \text{ lb/ft}^2$ )
- No penetration, ballast or racking required.
- Applicable for high wind load and high shading losses.
- Bypass diodes reduce PV system shading losses.
- Directly bonds to many approved surfaces.

### Reliability and safety

- IEC 61646, IEC 61730-1 & -2, IEC 61701, IEC 62716, DEWA.
- UL 1703, ULC ORD C 1703, UL 2703.
- 5 years workmanship.
- 10/25 years warranty against power loss.



## FLEX SERIES

### SP-FWSP- CIGS MODULE SERIES

#### Electrical performance AT STC<sup>1</sup>

| Nominal Power PMPP              | (W) | 85       | 90    | 100   | 150   | 180   |
|---------------------------------|-----|----------|-------|-------|-------|-------|
| Power Output Tolerance          | (W) | +5/-0    | +5/-0 | +5/-0 | +5/-0 | +5/-0 |
| Maximum Power Voltage VMPP      | (V) | 18.44    | 24.84 | 18.2  | 18.8  | 22.23 |
| Maximum Power Current IMPP      | (A) | 4.72     | 3.71  | 5.49  | 7.96  | 8.08  |
| Open Circuit Current VOC        | (V) | 22.7     | 30.64 | 22.47 | 22.5  | 26.5  |
| Short Circuit Current ISC       | (A) | 5.28     | 4.19  | 5.93  | 8.38  | 8.38  |
| Maximum Series Fuse Rating      | (A) | 10       |       |       | 15    |       |
| Maximum System Voltage (IEC/UL) | (V) | 1000/600 |       |       |       |       |


<sup>1</sup>Standard Test Conditions (STC): 1000 W/m<sup>2</sup>, 77°F cell temperature, AM 15 spectrum.

#### Thermal Characteristics

| NOCT                         | (°F)   | 118.4 |
|------------------------------|--------|-------|
| Temperature Coefficient PMPP | (%/°F) | 32.68 |
| Temperature Coefficient VOC  | (%/°F) | 32.50 |
| Temperature Coefficient ISC  | (%/°F) | 32.01 |

#### Physical and Mechanical Specifications

| Length                    | 6.56'                                                                                    | 4.92'    | 4.92'    | 4.92'    | 5.74'    |
|---------------------------|------------------------------------------------------------------------------------------|----------|----------|----------|----------|
| Outside Diameter          | 4.72"                                                                                    | 5.51"    | 6.29"    | 8.62"    | 8.62"    |
| Inside Pole Diameter      | No need                                                                                  | No need  | <4.25"   | <4.49"   | <4.49"   |
| Thickness with mold       | 0.09"                                                                                    | 0.09"    | 0.09"    | 0.17"    | 0.17"    |
| Weight with aluminum mold | 22.66lbs                                                                                 | 18.62lbs | 20.83lbs | 31.96lbs | 37.36lbs |
| Junction Box Type         | IP68                                                                                     |          |          |          |          |
| Cell Type                 | Copper Indium Gallium Di selenide (CIGS)                                                 |          |          |          |          |
| Certifications            | UL 1703, ULC ORD C1703, UL 2703, IEC 61646, IEC 61730-1 & -2, IEC 61701, IEC 62716, DEWA |          |          |          |          |



## SOLAR STREET LIGHT

---

### USES AND APPLICATIONS GUIDE

|                   |   |
|-------------------|---|
| Streets Lighting  | V |
| Parking Lots      | V |
| Residential Roads | V |
| Public Parks      | V |
| Sports Lighting   | V |

## ORDERING GUIDE

Ordering Guide: EXAMPLE: HIGHLIGHT SP-WPTX-A-85W-20W-3-30K-20AH-XXFT-GR-00

| Model     | Solar Panel Quantity | Solar Panel | Led Power | Distribution Type | Led Color Temp | Battery capacity | Pole Height | Body Color                           | Options                 |
|-----------|----------------------|-------------|-----------|-------------------|----------------|------------------|-------------|--------------------------------------|-------------------------|
| HIGHLIGHT | A - 1 panel          | 85W         | 20W       | 2 – Type II       | 30K            | 20AH             | XXFT        | GR- Grey                             | 00 – No Motion Sensor   |
| SP-WPTX   | B - 2 panels         | 90W         | 30W       | 5 – Type V        | 40K            | 40AH             |             | BLK- Black                           | 01 – With Motion Sensor |
|           | C – 3 Panels         | 100W        | 40W       |                   | 50K            | 60AH             |             | *Other colors available upon request |                         |
|           | D – 4 Panels         | 150W        | 50W       |                   | 60K            | 100AH            |             |                                      |                         |
|           |                      | 180W        |           |                   | Amber          | 120AH            |             |                                      |                         |
|           |                      |             |           |                   | 150AH          |                  |             |                                      |                         |



\*Up on request

Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other than downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage





## Contact us



+1.201.490.4499

Toll free: 1.888.333.SOLAR (7652)



[contact@solarpathusa.com](mailto:contact@solarpathusa.com)



[www.solarpathusa.com](http://www.solarpathusa.com)