

SP-SEP Specifications



Why us?

Innovative Technology

High-efficiency solar and advanced LEDs deliver superior performance, long life, and maximum ROI.

Photometric

We conduct photometric measurements on all our products to ensure optimal performance and compliance with industry standards

Versatile Lighting

We design and install solar-powered lighting systems tailored for all kinds of locations such as streets, parks, pathways, homes, etc.

Global Reach

Worldwide success proves our adaptability and regulatory expertise.

Sustainable Savings

These solutions enhance safety, promote sustainability and provide significant energy and cost savings.

Warranty

SolarPath is dedicated to delivering architectural and commercial-grade solar lighting that can be customized to meet specific client requests, both in technical specifications and aesthetic design, ensuring a perfect fit for a diverse range of needs.



The SolarPath SP-SEP™ is the most advanced and sophisticated solar engine pole that supplies power that is available on the market. The solar light pole is completely off-grid and works autonomously, using sustainable solar power. This means there is no need for expensive cabling and invasive trenching. This results in fast installation, easy operation and a low total cost of ownership. Solar energy generated during the day is stored in high-quality lithium batteries, which are long-lasting and requires minimum maintenance. A solar engine pole provides low voltage and you can connect devices such as solar security cameras, LED lighting, mobile devices charging, bike charging and much more.

Technical specification

Solar Module Parameters	Type	CIGS Amorphous flexible solar panel wrap on pole
	Power	Up to 720W
	Amount of solar modules	Up to 4 pcs
Solar Charge Controller	MPPT (Maximum Power Point Tracking), infrared solar charging controller	
Battery	LifePO	Up to 150AH
IP Rating	IP65	
Operation Temperature	-4°F~131°F	
Pole Height	Customized per to customer requirement	



FLEX SERIES -1.7N

CIGS Flexible Modules:
High Power Density in a Flexible Form Factor

Solar cylindrical wrap pole panel data sheet

Key Features

- Record efficiency level in a CIGS flexible form factor.
- Low installed weight at less than 2.9 kg/m² (<0.6lb/ft²)
- No penetration, ballast or racking required.
- Applicable for high wind load and high shading losses.
- Bypass diodes reduce PV system shading losses.
- Directly bonds to many approved surfaces.

Reliability and safety

- IEC 61646, IEC 61730-1 & -2, IEC 61701, IEC 62716, DEWA.
- UL 1703, ULC ORD C 1703, UL 2703.
- 5 years workmanship.
- 10/25 years warranty against power loss.



FLEX SERIES

SP-FWSP- CIGS MODULE SERIES

Electrical performance AT STC¹

Nominal Power PMPP	(W)	85	90	100	150	180
Power Output Tolerance	(W)	+5/-0	+5/-0	+5/-0	+5/-0	+5/-0
Maximum Power Voltage VMPP	(V)	18.44	24.84	18.2	18.8	22.23
Maximum Power Current IMPP	(A)	4.72	3.71	5.49	7.96	8.08
Open Circuit Current VOC	(V)	22.7	30.64	22.47	22.5	26.5
Short Circuit Current ISC	(A)	5.28	4.19	5.93	8.38	8.38
Maximum Series Fuse Rating	(A)	10			15	
Maximum System Voltage (IEC/UL)	(V)	1000/600				

¹Standard Test Conditions (STC): 1000 W/m², 77°F cell temperature, AM 15 spectrum.

Thermal Characteristics

NOCT	(°F)	118.4
Temperature Coefficient PMPP	(%/°F)	32.68
Temperature Coefficient VOC	(%/°F)	32.50
Temperature Coefficient ISC	(%/°F)	32.01

Physical and Mechanical Specifications

Length	6.56'	4.92'	4.92'	4.92'	5.74'
Outside Diameter	4.72"	5.51"	6.29"	8.62"	8.62"
Inside Pole Diameter	No need	No need	<4.25"	<4.49"	<4.49"
Thickness with mold	0.09"	0.09"	0.09"	0.17"	0.17"
Weight with aluminum mold	22.66lbs	18.62lbs	20.83lbs	31.96lbs	37.36lbs
Junction Box Type	IP68				
Cell Type	Copper Indium Gallium Di selenide (CIGS)				
Certifications	UL 1703, ULC ORD C1703, UL 2703, IEC 61646, IEC 61730-1 & -2, IEC 61701, IEC 62716, DEWA				



SOLAR STREET LIGHT

USES AND APPLICATIONS GUIDE

Security Camera

Streets Lighting

Parking Lots

Residential Roads

Public Parks

Sports Lighting

ORDERING GUIDE

Ordering Guide: EXAMPLE: SP-SEP-A-85W-30AH-10FT-GR-SC

Model	Solar panel qty.	Solar panel	Battery capacity	Pole height	Body color	Options
SP-SEP	A – 1 panel	85W	30AH	10 FT	BLK-Black	SC- Security Camera
	B – 2 panels	90W	40AH	13FT	GR-Grey	
	C – 3 panels	100W	50AH	16FT	*other colors available upon request	
	D – 4 panels	150W	60AH	20FT		
		180W	80AH	23FT		
			100AH	26FT		
			120AH	29FT		
			150AH	32FT		

*Final part number will provide by the manufacturer.



*Up on request

Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage



Contact us



+1.201.490.4499

Toll free: 1.888.333.SOLAR (7652)



contact@solarpathusa.com



www.solarpathusa.com