

SP-SLSP Specifications



Why us?

Innovative Technology

High-efficiency solar and advanced LEDs deliver superior performance, long life, and maximum ROI.

Photometric

We conduct photometric measurements on all our products to ensure optimal performance and compliance with industry standards

Versatile Lighting

We design and install solar-powered lighting systems tailored for all kinds of locations such as streets, parks, pathways, homes, etc.

Global Reach

Worldwide success proves our adaptability and regulatory expertise.

Sustainable Savings

These solutions enhance safety, promote sustainability and provide significant energy and cost saving.

Warranty

SolarPath is dedicated to delivering architectural and commercial-grade solar lighting that can be customized to meet specific client requests, both in technical specifications and aesthetic design, ensuring a perfect fit for a diverse range of needs.



The SolarPath SP-SLSP™ is the most advanced and sophisticated solar LED sign light pole available on the market. The solar light sign pole is completely off-grid and works autonomously, using sustainable solar power. This means there is no need for expensive cabling and invasive trenching, which results in fast installation, easy operation, and a low total cost of ownership. Solar energy generated during the day is stored in high-quality lithium batteries, which are long-lasting and require minimum maintenance. The highly efficient LED-luminaire provides powerful lighting at night. Sign is customized per the customer requirement. Solar sign lighting systems can be used for commercial, residential or neighborhood signs, and for internal or external illumination.

Technical specification

Solar Module Parameters	Type	CIGS Amorphous flexible solar panel wrap on pole
	Power	Up to 360W
	Amount of solar modules	Up to 2 pcs
Solar Charge Controller	MPPT (Maximum Power Point Tracking), infrared solar charging controller	
Battery	LifePO	Up to 20AH
LED Light Parameters	Light Source Power	Up to 15W
	CCT (Correlated color temp.)	3,000K-6,000K
Operation profile	Dusk to Dawn (dim per to solar radiation)	
IP Rating	IP65	
Operation Temperature	-4°F~131°F	
Pole Height	Customized per to customer requirement	



FLEX SERIES -1.7N

CIGS Flexible Modules:
High Power Density in a Flexible Form Factor

Solar cylindrical wrap pole panel data sheet

Key Features

- Record efficiency level in a CIGS flexible form factor.
- Low installed weight at less than 2.9 kg/m^2 ($<0.6 \text{ lb/ft}^2$)
- No penetration, ballast or racking required.
- Applicable for high wind load and high shading losses.
- Bypass diodes reduce PV system shading losses.
- Directly bonds to many approved surfaces.

Reliability and safety

- IEC 61646, IEC 61730-1 & -2, IEC 61701, IEC 62716, DEWA.
- UL 1703, ULC ORD C 1703, UL 2703.
- 5 years workmanship.
- 10/25 years warranty against power loss.



FLEX SERIES

SP-FWSP- CIGS MODULE SERIES

Electrical performance AT STC¹

Nominal Power PMPP	(W)	85	90	100	150	180
Power Output Tolerance	(W)	+5/-0	+5/-0	+5/-0	+5/-0	+5/-0
Maximum Power Voltage VMPP	(V)	18.44	24.84	18.2	18.8	22.23
Maximum Power Current IMPP	(A)	4.72	3.71	5.49	7.96	8.08
Open Circuit Current VOC	(V)	22.7	30.64	22.47	22.5	26.5
Short Circuit Current ISC	(A)	5.28	4.19	5.93	8.38	8.38
Maximum Series Fuse Rating	(A)	10			15	
Maximum System Voltage (IEC/UL)	(V)	1000/600				


¹Standard Test Conditions (STC): 1000 W/m², 77°F cell temperature, AM 15 spectrum.

Thermal Characteristics

NOCT	(°F)	118.4
Temperature Coefficient PMPP	(%/°F)	32.68
Temperature Coefficient VOC	(%/°F)	32.50
Temperature Coefficient ISC	(%/°F)	32.01

Physical and Mechanical Specifications

Length	6.56'	4.92'	4.92'	4.92'	5.74'
Outside Diameter	4.72"	5.51"	6.29"	8.62"	8.62"
Inside Pole Diameter	No need	No need	<4.25"	<4.49"	<4.49"
Thickness with mold	0.09"	0.09"	0.09"	0.17"	0.17"
Weight with aluminum mold	22.66lbs	18.62lbs	20.83lbs	31.96lbs	37.36lbs
Junction Box Type	IP68				
Cell Type	Copper Indium Gallium Di selenide (CIGS)				
Certifications	UL 1703, ULC ORD C1703, UL 2703, IEC 61646, IEC 61730-1 & -2, IEC 61701, IEC 62716, DEWA				



SOLAR STREET LIGHT

USES AND APPLICATIONS GUIDE

Streets name pole

Parking Lots

Residential Roads

Public Parks

Sports Lighting

ORDERING GUIDE

Ordering Guide: EXAMPLE: SP-SEP-A-85W-30AH-10FT-GR-SC

Model	Solar panel qty.	Solar panel	LED Power	Color Temperature	Battery capacity	Pole height	Body color	LED Location
SP-SLSP	A – 1 panel	85W	15W	30K	20AH	10 FT	BLK-Black	TP- Top of the pole
	B – 2 panels	90W		40K	40AH	15FT	GR-Grey	MP- Middle of the pole
		100W		60K			*other colors available upon request	
		150W						
		180W						



*Up on request

Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage



Contact us



+1.201.490.4499

Toll free: 1.888.333.SOLAR (7652)



contact@solarpathusa.com



www.solarpathusa.com